

## Broadcast Camera Li-ion Battery



- ◆ New high power Li-ion cells.
- ◆ D-tap output socket.
- ◆ 5-level LED power indicator.
- ◆ V-Mount plate/Gold Mount plate.
- ◆ Multiple circuit protections.



RED Cinema Camera



Panasonic ENG Camera



SONY ENG Camera



Blackmagic Cinema Camera

### IATA Complied Separable Li-ion Battery

The IATA DGR regulations restricted the air transportation of over 100Wh Li-ion battery packs:

Battery Capacity	Carry-on Baggage	Air Cargo Shipping
Under 100Wh	OK	OK
100Wh-160Wh	Only 2pcs allowed	Not allowed
Over 160Wh	Not allowed	Not allowed

Since the large capacity batteries are quite necessary, LITH provides the solution of Dividable Battery to comply with IATA regulations.

## Broadcast Camera Li-ion Battery



### #:L-75S 75Wh Mount Type:V-Mount

Voltage:14.4V  
Capacity:75Wh/5.2Ah  
Max Output Power:50W  
Max Output Current:3.5A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 0.70kg  
Dimension:164x90.3x51.5mm



### #:L-75A 75Wh Mount Type:Gold Mount

Voltage:14.4V  
Capacity:75Wh/5.2Ah  
Max Output Power:50W  
Max Output Current:3.5A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 0.70kg  
Dimension:164x90.3x56.5mm



### #:L-95S 95Wh Mount Type:V-Mount

Voltage:14.4V  
Capacity:95Wh/6.6Ah  
Max Output Power:50W  
Max Output Current:3.5A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 0.85kg  
Dimension:164x90.3x51.5mm



### #:L-95A 95Wh Mount Type:Gold Mount

Voltage:14.4V  
Capacity:95Wh/6.6Ah  
Max Output Power:50W  
Max Output Current:3.5A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 0.85kg  
Dimension:164x90.3x56.5mm



### #:L-110S 110Wh Mount Type:V-Mount

Voltage:14.4V  
Capacity:110Wh/7Ah  
Max Output Power:50W  
Max Output Current:3.5A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 0.70Kg  
Dimension:164x90.3x51.5mm



### #:L-110A 110Wh Mount Type:Gold Mount

Voltage:14.4V  
Capacity:110Wh/7Ah  
Max Output Power:50W  
Max Output Current:3.5A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 0.72Kg  
Dimension:164x90.3x56.5mm

## Broadcast Camera Li-ion Battery



### #:L-130S 130Wh Mount Type:V-Mount

Voltage:14.4V  
Capacity:130Wh/9Ah  
Max Output Power:70W  
Max Output Current:5A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 0.95Kg  
Dimension:164x90.3x51.5mm



### #:L-130A 130Wh Mount Type:Gold Mount

Voltage:14.4V  
Capacity:130Wh/9Ah  
Max Output Power:70W  
Max Output Current:5A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 0.97Kg  
Dimension:164x90.3x56.5mm



### #:L-160S 160Wh Mount Type:V-Mount

Voltage:14.4V  
Capacity:160Wh/11Ah  
Max Output Power:100W  
Max Output Current:8A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 1.15Kg  
Dimension:164x90.3x63.4mm



### #:L-160A 160Wh Mount Type:Gold Mount

Voltage:14.4V  
Capacity:160Wh/11Ah  
Max Output Power:100W  
Max Output Current:8A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 1.17Kg  
Dimension:164x90.3x68.4mm



### #:L-190S 190Wh Mount Type:V-Mount

Voltage:14.4V  
Capacity:190Wh/13.2Ah  
Max Output Power:100W  
Max Output Current:8A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 1.30Kg  
Dimension:164x90.3x63.4mm



### #:L-190A 190Wh Mount Type:Gold Mount

Voltage:14.4V  
Capacity:190Wh/13.2Ah  
Max Output Power:100W  
Max Output Current:8A  
Over Current Protection:10A  
Operation temperature:-30°C~+50°C  
Net Weight:Approx 1.32Kg  
Dimension:164x90.3x68.4mm